

Product Data Sheet

# DIY Final Finish Topping Compound



Gyprock Final Finish is a heavyweight topping compound used as a top coat in a three coat plasterboard jointing system.

## Product Overview

Final Finish Topping Compound is a pre-mixed, low VOC finishing compound for joints and angles in plasterboard and fibre cement walls and ceilings. It is specifically formulated to provide a smooth and easy to sand finish to joints in preparation for painting and is not recommended for bedding tapes and second coats.

## Typical Applications

Final Finish Topping Compound is used as the topping coat in a 3 coat plasterboard or fibre cement jointing system. It is ideal for use in internal walls and ceilings and as a topping compound over Wet Area Base Coat in areas subject to moisture or high humidity.



### Smooth Finish

Excellent sandability



### Easy Application

Premixed for easy application



### DIY Range

Professional quality in convenient pack sizes

## Technical Specifications

### Product Options

Gyprock Final Finish Topping Compound is available in 3kg pails with a shelf life of 1 year from date of manufacture.

For product availability and to place an order, contact your nearest supplier.

### Physical & Chemical Properties

Coverage kg/100m <sup>2</sup>	1kg
Specific gravity (H <sub>2</sub> O=1)	1.6 - 2.0
VOC content (as specified by GBCA)	<10 grams per Litre as VOC content per material

### Product Manufacture

Gyprock Final Finish Topping Compound is manufactured by CSR Gyprock in Australia to stringent product specifications.

### Product Handling

**Transportation and manual handling:** Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

**Storage:** Store buckets of compound in a dry environment out of direct sunlight. Remove lid and stir prior to use. Unused product should be stored by resealing the original bucket. Remix prior to use. Discard if drying has commenced.

### Health and Safety

**Safety Data Sheets** are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

## Installation Instructions

### Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

### Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.



#### Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



#### GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Adhesives, Fillers & Sealants standard.



#### Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.