

Product Data Sheet

# Rapid Set

Specially formulated for use in Western Australia, Rapid Set is a quick drying all-purpose jointing compound for use on small-scale jointing jobs and patching.

## Product Overview

Rapid Set is a plaster based all-purpose compound used as all coats in a three coat jointing system or as a base coat only. This low VOC dry powder has been engineered with a rapid 20 minute working time after mixing. This makes it ideal for jobs which need to be completed in one day. Coats should be allowed to harden and dry for at least 30 minutes before re-coating or sanding.

## Typical Applications

Gyprock Rapid Set is typically used as all coats in a three coat jointing system for plasterboard and fibre cement in smaller residential and commercial walls and ceiling projects. It is also ideal for patching holes and defects. Hand application is recommended given the short working time.



### Rapid Setting

20 minute working time



### All-purpose

Use for all coats of a 3 coat joint system



### Repairs and Maintenance

Great for patching holes and defects

# Technical Specifications

## Product Options

Gyprock Rapid Set is available in a 10kg bag with a shelf life is 1 year from manufacture

For product availability and to place an order, contact your nearest supplier.

## Physical & Chemical Properties

Specific gravity (H <sub>2</sub> O=1)	2.3 - 2.4
VOC content (as specified by GBCA)	<10 g/L as VOC content per material

## Product Manufacture

Gyprock Rapid Set is manufactured by CSR Gyprock in Australia to stringent product specifications.

## Product Handling

**Transportation and manual handling:** Refer to the Gypsum Board Manufacturers of Australia (GBMA) website for recommended OH&S practices.

**Storage:** Store bags of compound in a dry environment, protected from the weather and out of direct sunlight. Tear bag open from top corner to dispense compound. Unused product which has been mixed with water should be discarded. Unused product in powder format should be stored in original bag: roll the top of the bag to loosely seal, and store in an airtight container.

## Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

## Installation Instructions

### Installing to Standards

AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.



#### Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



#### Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.

### Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.