



Product Data Sheet

Standard 13mm

This board sets the Standard for commercial applications. Gyprock Standard 13mm works as a general internal wall and ceiling lining in a huge range of commercial applications.

Product Overview

Gyprock Standard 13mm is manufactured in Australia to meet and exceed the requirements of Australian Standard AS/NZS 2588.

The go-to for commercial construction, Gyprock Standard 13mm can also be used residential to deliver a more robust, acoustically sound lining.

Typical Applications

Gyprock Standard 13mm is typically used as a wall and ceiling lining option in commercial applications including non-fire or acoustic rated walls and partitions.



Versatile

Suitable for walls and ceilings



Excellent Score and Snap

Easier to use



25 Year Warranty

Specify and install with confidence

Technical Specifications

Product Options

Gyprock Standard 13mm is available in the following sizes:

| | |
|---------------|--|
| Thickness | 13mm |
| Widths | 900mm 1200mm 1350mm 1400mm |
| Lengths | 2400mm 2700mm 3000mm 3600mm 4200mm 4800mm 6000mm |
| Edge Profiles | Recessed Edge for regular jointing Recessed Edge/Square Edge for low profile architectural mouldings Square Edge for applications not requiring jointing |

Stockholdings may vary. For product availability and to place an order, contact your nearest supplier.

Product Manufacture

Gyprock Standard 13mm is manufactured by CSR Gyprock in Australia to stringent product specifications.

Product Handling

Transportation and manual handling: Refer to the [Gypsum Board Manufacturers of Australia \(GBMA\) website](#) for recommended OH&S practices.

Storage: Protect plasterboard and cornice from weather and moisture. Avoid products sagging by storing horizontally, supported on a level platform or full-width support members spaced at max. 600mm centres.

Health and Safety

Safety Data Sheets are important documents in the construction industry and assist in the continuing focus on occupational health and safety on and off sites.

Manufacturing Tolerances

| | |
|-------------------|--|
| Nominal Thickness | 13mm ± 0.5mm |
| Nominal Widths | 900, 1200, and 1350mm ± 3mm |
| Nominal Lengths | From 2400 to 6000mm ± 5mm, typically in 300mm increments |
| Squareness | Cut ends ± 3mm in the width of the board |

Physical Properties

| | |
|---|---|
| Nominal Board Weight* | 8.5kg/m ² |
| Thermal Performance: R-Value | 0.05 - 0.07 m ² K/W |
| Fire Hazard: assessed to AS/NZS3837 cone calorimeter test | Average Specific Extinction Area (ASEA) <250m ² /kg Group Number 1 Report Reference WFRA 45759 |
| Combustibility | In accordance with BCA Clause C1.12, Gyprock Standard 13mm may be used wherever a non-combustible material is required by the Code. |
| Total Recycled Content | 3.7% |

*Subject to reasonable manufacturing variance.

Installation Instructions

Installation Guidance

Install to manufacturer's recommendations as outlined in the relevant Installation Guide.



Manufactured for Life

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.



GECA Accredited

Verified by an independent conformity assessment body to meet the environmental, health and social/ethical criteria of the GECA Panel Boards standard.

Resources

Gyprock makes available [resources](#) that provide comprehensive selection, design, installation and maintenance guidance.



Australian Standard

Exceeds the requirements of Australian Standard AS/NZS 2588 - Gypsum Plasterboard, accredited through SAI Global.



Certified Low VOC

Exceeds the GBCA specification for Volatile Organic Compound content according to independent testing.